




SPECIFICATION



RATING:	16(8)A 250V~ T85,8/128A 250V~ T85(UL, CUL,ENEC)
	TV-8 250V~ 25E3 (UL,CUL)
INSULATION RESISTANCE:	DC 500V 100MΩ OR MORE
CONTACT RESISTANCE:	DC 2-4V 1A 20mΩ OR LESS
WITHSTAND VOLTAGE:	AC 1500V FOR 1 Min
AMBIENT TEMPERATURE:	0~85°C
ELECTRICAL LIFE:	25,000 CYCLES

SIZE



W	PANEL THICK
19.2	0.75 ~ 1.25
19.4	1.25 ~ 2.00
19.8	2.00 ~ 3.00

MOUNTING HOLE
(FOR REFERENCE)




W	PANEL THICK
19.2	0.75 ~ 1.25
19.4	1.25 ~ 2.00
19.8	2.00 ~ 3.00

MOUNTING HOLE
(FOR REFERENCE)

HOW TO ORDER

3024 - [] - [] - [] - [] - [] - [] - [] - []

Knob



Print

P1:	P11:
P2:	P12:
P3:	P13:
P4:	P14:
P5:	P15:
P6:	P16:
P7:	
P8:	
P9:	
P10:	

Terminal

T1: t0.8x4.0	T11: ø1.4
T2: t0.8x4.75	T12: ø2.4
T3:	T14:
T4:	T15:
T6:	T16:
T7:	T17:
T8:	T19:
T9: T1内径 20'	T20:
T10: t0.8x4.75	

Circuit

S: SPST
D: DPST

Body

NONE	B10:
B03:	B12:
B04:	B13:
B05:	
B07:	
B08:	

Knob Color

BK: BLACK
GY: GRAY
RD: RED
SW: SNOW WHITE
WT: WHITE
YW: YELLOW WHITE

Body Color

BK: BLACK
GY: GRAY
SW: SNOW WHITE
WT: WHITE
YW: YELLOW WHITE